



HOZ-03462/24-001323-420/078.00 Article No.:462-1209

General

Enclosure: Open	Special feature: forcibly guided contact set	Connections: Soldering pins
Contact set (NO/NC/CO) 420	Dimensions: 67,4x20,5x48,6 mm	Weight: 105 g

Technical Data $T_u = 20^\circ\text{C}$

Switching voltage,max	AC 230/240 V	DC 300 V
Switch. capacity,max 2.000/120 VA/W	Switching current,max 10 A	Constant current,max 10 A
Contact resistance < 100mOhm		
Endurance,mech. > 1x10 ⁷	Endurance,electr.	> 10 ⁵ Switching cycles
Switching capacity	AC15 230/240 V, I _e	DC13 24 V, I _e
AgCdO-10 / 0,2 μm Au	4 A	1,6 A

Insulation	AC 120 V	AC 240 V	AC 230 V	AC 400 V	Test voltage
contact-contact	D-I	D-I	B-I	B-I	2.500V
contact sets - drive	D-I	D-I	B-I	B-I	2.500V

D-I = Reinforced (double) insulation B-I = Basic insulation

Switch time energizing with 1,5*U_i

t _{a-nc}	t _{a-no}	t _{r-no}	t _{r-nc}
20 ms	28 ms	3,8 ms	6,5 ms
Shock resistance at 11 ms 10 g		Vibration resistance at 10-100 Hz 10 g	
Ambient temperature -25...+80°C			

Operating voltage

T _u /°C	coil I: R = 110,0 Ohm				U _{enn} +10/ -15%		V
	U ₁	U ₂	U ₃	U _{rück}	min	max	
20	6,9	21,2	19,2	1,4	8,4	19,2	V
-5	6,2	23,1	17,3	1,2	7,6	21,0	V
20	6,9	21,2	19,2	1,4	8,4	19,2	V

Quoted data does not represent any binding characteristics and may be subject to technical alterations.

Hengstler GmbH GB Bauelemente, Postfach 1249, D - 78 561 Wehingen, Tel: + 49 (7426) 68-0, Fax: + 49 (7426) 68-281