



HOZ-03463/11-001620-310/031.00 Article No.:463-1014

General

Enclosure: Open	Special feature: forcibly guided contact set	Connections: Soldering pins
Contact set (NO/NC/CO) 310	Dimensions: 42,7x16x38,8 mm	Weight: 40 g

Technical Data $T_u = 20^\circ\text{C}$

Switching voltage,max	AC 230/240 V	DC 60 V
Switch. capacity,max 1.200/50 VA/W	Switching current,max 6 A	Constant current,max 6 A
Contact resistance < 50 mOhm		
Endurance, mech. > 1x10 ⁷	Endurance, electr.	1,5x10 ⁵ Switching cycles
Switching capacity	AC15 230/240 V, I _e	DC13 24 V, I _e
AgCdO-10 / 0,2 μm Au	1,5 A	1,2 A

Insulation	AC 120 V	AC 240 V	AC 230 V	AC 400 V	Test voltage
contact-contact	D-I	D-I	B-I	B-I	2.500V
contact sets - drive	D-I	D-I	B-I	B-I	2.500V

D-I = Reinforced (double) insulation B-I = Basic insulation

Switch time energizing with 1,5*U_i

t _{a-nc}	t _{a-no}	t _{r-no}	t _{r-nc}
10 ms	14 ms	3,5 ms	4,5 ms
Shock resistance at 11 ms	10 g	Vibration resistance at 10-100 Hz	15 g
			Ambient temperature -25...+80°C

Operating voltage

T _u /°C	coil I: R = 130,0 Ohm				U _{nenn} +10/ -15%			
	U ₁	U ₂	U ₃	U _{rück}	min	max		
20	8,0	20,7	22,8	1,6	9,9	18,8		V
-5	7,2	22,6	20,5	1,4	9,0	20,6		V
20	8,0	20,7	22,8	1,6	9,9	18,8		V

Quoted data does not represent any binding characteristics and may be subject to technical alterations.

Hengstler GmbH GB Bauelemente, Postfach 1249, D - 78 561 Wehingen, Tel: + 49 (7426) 68-0, Fax: + 49 (7426) 68-281