



HDZ-43468/11-001082-310/001.00 Article No.:468-1003

General

Enclosure: Sealed	Special feature: forcibly guided contact set	Connections: Soldering pins
Contact set (NO/NC/CO) 310	Dimensions: 42x12,5x30 mm	Weight: 35 g

Technical Data $T_u = 20^\circ\text{C}$

Switching voltage,max	AC 230/240 V	DC 300 V
Switch. capacity,max 1.500/30 VA/W	Switching current,max 8 A	Constant current,max 6 A
Contact resistance < 50mOhm		
Endurance,mech. > 1x10 ⁷	Endurance,electr.	10 ⁵ Switching cycles
Switching capacity	AC15 230/240 V, I _e	DC13 24 V, I _e
AgNi-10 / 0,2 µm Au	4 A	1,6 A

Insulation	AC 120 V	AC 240 V	AC 230 V	AC 400 V	Test voltage
contact-contact	D-I	D-I	B-I	B-I	2.000V
contact sets - drive	D-I	D-I	B-I	B-I	2.500V

D-I = Reinforced (double) insulation B-I = Basic insulation

Switch time energizing with 1,5*U_I

t _{a-nc}	t _{a-no}	t _{r-no}	t _{r-nc}
14 ms	17 ms	10 ms	14 ms
Shock resistance at 11 ms 10 g		Vibration resistance at 10-100 Hz 5 g	
Ambient temperature -40...+85°C			

Operating voltage

T _u /°C	coil I: R = 1020,0 Ohm				U _{nenn} +10/ -15%		V
	U ₁	U ₂	U ₃	U _{rück}	min	max	
20	18,1	50,4	147,7	4,7	22,2	45,8	V
-5	17,3	55,3	139,8	3,5	21,3	50,3	V
20	18,1	50,4	147,7	4,7	22,2	45,8	V

Quoted data does not represent any binding characteristics and may be subject to technical alterations.

Hengstler GmbH GB Bauelemente, Postfach 1249, D - 78 561 Wehingen, Tel: + 49 (7426) 68-0, Fax: + 49 (7426) 68-281