

# HENGSTLER OVERVIEW

462

463 (467)

468

464 (466)



Outline Dimensions  
L x W x H (mm)

58 (68) x 20.5 x 48.6

42.7 x 16 x 38.8

42 (35) X 12.5 X 30

77.4 (87.4) x 20.5 x 48.6

## Contact Data

<b>Contact Arrangement</b>	3 NO/1 NC 2 NO/2 NC 4 NO/2 NC 3 NO/3 NC	3 NO/1 NC 2 NO/2 NC	1 NO/1 NC (469) 2 NO/2 NC 3 NO/1 NC	2 NO/6 NC - 8 NO/2 NC 6 NO/4 NC - 7 NO/3 NC 4 NO/4 NC - 5 NO/3NC 3 NO/5 NC - 6 NO/2NC
<b>Standard Contact Material</b>	Ag Cd 0- 0.2µ Au Ag Cd 0- 5µ Au Ag Sn 02- 5µ Au	Ag Cd 0- 0.2µ Au Ag Cd 0- 5µ Au	Ag Cd 0- 0.2µ Au Ag Ni 10 - 2µ Au	Ag Cd 0- 0.2µ Au Ag Cd 0- 5µ Au
<b>Maximum Switching Voltage</b>	230/240/ AC / 230 DC	230/240/ AC / 60 DC	230/240/ AC / 250 DC	230/240/ AC / 230 DC
<b>Maximum Switching Current</b>	10	6	6	10
<b>Maximum Load Resistive (VA)</b>	2000	1200	1500	2000

## Coil Data

<b>Nominal Voltage</b>	6 - 220 DC	6 - 220 DC	6 - 110 DC	6 - 220V
<b>Coil Power (Watts)</b>	1.2	1.1	0.666	1.0
<b>Maximum Resistance (Ohms)</b>	40,000	25,000	18.860	1,200

## Approvals

TUV, SEV,  
SULA, SA,  
SEMKO,  
UL, CSA

TUV, UL,  
CSA

VDE, TUV,  
UL

TUV, SUVA,  
SA, UL,  
CSA, BZA